



# MOT - 185 ADVANCED

### **ELECTRICAL CHARACTERISTICS**

Power Supply: 240V / 400VHeating element: 3750W

#### **ULTRASONIC CHARACTERISTICS**

- Ultrasonic power: 1800Wp (3600W p-p)
- 1 ultrasonic generator with an output power of 1800Wp (3600W p-p)
- 1 submersible emitter with a power of 1800W (3600W p-p)made of 2.5 mm thick stainless steel AISI 316. The emitter contains 36 PZT (lead zirconate titanate) piezo-electric transducers with aluminium alloy body.
- Working frequency: 40 KHz sweep system ± 2%

#### **CONTROL PANEL**

- 7" Screen & TFT Display. Time control for equipment preheating, weekly calendar, alarms, US direct selectors, heating resistance, platform lift and lowering, continues vertical motion up and down system and water level control.
- 6 outputs and 8 inputs temperature module PLC

## FINISH AND ACCESORIES

- Tank made of 2 mm thick stainless steel INOX AISI 304
- Polypropylene external panel
- 20 mm thick thermo-acoustic insulation
- Reinforced pneumatic platform for loading and unloading up to 60 kg
- Opening-closing lid in polypropylene with double wall of 4 mm thickness and thermal-acoustic insulation
- · Air blow gun for drying the parts
- Integrated waterflow system. Sweeps the waste floating on the surface, keeping the cleaning equipment in perfect condition
- (Optional): Filtration system (stainless steel filter with polypropylene / polyester bag) for waste and mud

#### **TECHNICAL DATA**

- · Capacity: 185 litres
- Internal dimensions: 760x520x595 mm
- Useful dimensions: 730x455x310 mm
- External dimensions: 1190x940x920 (1760 Total) mm
- · Weight: 175 kg



WARRANTY AND PRODUCT QUALITY: All equipments supplied by TierraTech®, are supplied with an instruction manual in English according to the European legislation on CE marking. The equipments comply the directives on electromagnetic compatibility and electrical safety:

Directive 2004/108/EC and Directive 2006/95/ECThe equipments have 2 years warranty against manufacturing defects.