



# **MOT - 3000N**

# **3000 LITRES**

## **ELECTRICAL CHARACTERISTICS**

- · Power Supply: 400V
- · Heating element: 2x12000W

#### ULTRASONIC CHARACTERISTICS

- · Ultrasonic power: 16000Wp (32000W p-p)
- ultrasonic generators with an output power of 16000Wp (32000W p-p)
- 8 submersibles emitters with a power of 2000Wp (4000W p-p) made of 2.5 mm thick stainless steel AISI 316 steel, The emitter contains 34 PZT (lead zirconate titanate) piezo-electric transducers with aluminium alloy body.
- Working frequency: 40 KHz sweep system ± 2%

# CONTROL PANEL

- 4.3" touch screen. Functional and intuitive access to ultrasound time setting, temperature and peripheric or optional systems. Programmable weekly calendar
- 6 outputs and 8 inputs temperature module PLC

# FINISH AND ACCESORIES

- Tank made of 2 mm thick stainless steel AISI 304
- External panel in 1 mm thick fingerprint resistant steel
- 20 mm thick thermo-acoustic insulation
- Reinforced pneumatic platform for loading and unloading up to 1500 kg
- 1½" drain ball valve
- Height-adjustable silentblock legs
- · Automatic insulated tank cover in stainless steel operated by a pneumatic cylinder
- · Air blow gun for drying the parts
- Integrated waterflow system. Sweeps the waste floating on the surface, keeping the cleaning equipment in perfect condition
- · (Optional): Filtration system (stainless steel filter with polypropylene / polyester bag) for waste and mud

### TECHNICAL DATA

- · Capacity: 3000 litres
- Internal dimensions: 2050 x 1200 x 1205 mm
- Useful dimensions: 1930 x 1080 x 900 mm
- External dimensions: 3675 x 1800 x 1465 mm
- · Weight: 1850 kg



WARRANTY AND PRODUCT QUALITY: All equipments supplied by TierraTech®, are supplied with an instruction manual in English according to the European legislation on CE marking. The equipments comply the directives on electromagnetic compatibility and electrical safety:

Directive 2004/108/EC and Directive 2006/95/ECThe equipments have 2 years warranty against manufacturing defects.