

# **MOT - 600N**

# \*\*\*MotorClean

# **600 LITRES**

### **ELECTRICAL CHARACTERISTICS**

- Power Supply: 400V
- · Heating element: 9000W

## ULTRASONIC CHARACTERISTICS

- · Ultrasonic power: 6000Wp (12000Wp-p)
- •ultrasonic generators with an output power of 6000Wp (12000Wp-p)
- 3 submersibles emitters with a power of 2000W (4000Wp-p) made of 2.5 mm thick stainless steel AISI 316 steel. The emitter contains 34 PZT (lead zirconate titanate) piezo-electric transducers with aluminium alloy body.
- Working frequency: 40 KHz sweep system ± 2%

## CONTROL PANEL

- Touch screen (4,3 "), functional and intuitive, with access to selection of time of ultrasonic, temperature, security levels and peripheral systems.
- · Weekly calendar programming to optimize the start-up of the equipment.
- PLC with temperature module with 8 inputs and 6 outputs.

#### **FINISH AND ACCESORIES**

- Tank made of 2 mm thick stainless steel AISI 304
- External panel in 1 mm thick fingerprint resistant steel
- 20 mm thick thermo-acoustic insulation
- Reinforced pneumatic platform for loading and unloading up to 350 kg
- · 1½" drain ball valve
- · Height-adjustable silentblock legs
- Automatic insulated tank cover, in stainless steel, powered by pneumatic cylinder, with retainer, drip gutter and dead man safety system
- · Air blow gun for drying the parts
- · Integrated waterflow system. Sweeps the waste floating on the surface, keeping the cleaning equipment in perfect condition
- · (Optional): Filtration system (stainless steel filter with polypropylene / polyester bag) for waste and mud.

### **TECHNICAL DATA**

- · Capacity: 600 litres
- Internal dimensions: 1300 x 735 x 665 mm
- · Useful dimensions: 1230 x 650 x 430mm
- External dimensions: 2050 x 1200 x 1070 mm
- Weight: 400 kg

WARRANTY AND PRODUCT QUALITY: All equipments supplied by TierraTech®, are supplied with an instruction manual in English according to the European legislation on CE marking. The equipments comply the directives on electromagnetic compatibility and electrical safety:

Directive 2004/108/EC and Directive 2006/95/ECThe equipments have 2 years warranty against manufacturing defects.

MOT-600N (a) (b)